



Product Description

Capsuleline

Single-ended low-voltage halogen capsule giving crisp white halogen light

Benefits

- Low-pressure technology allows use in luminaires without front glass

Features

- Sturdy, low-pressure lamps with UV-Block glass (IEC 357)
- Gas-filled (≤ 2.5 bar) lamps can be used in luminaires without a front glass in accordance with IEC 598
- Axial filament for higher light output in combination with luminaires and a uniform beam
- Excellent colour rendering
- Universal burning position

Application

- Task lighting and decorative applications in homes, shops, hotels and restaurants

Related products



GY6.35, T11, Clear

General Information

order code	Bulb Shape	Cap-Base	Nominal Life-time (Nom)	Operating Position
41295950	T11	GY6.35	2000	UNIVERSAL

Light Technical

order code	Correlated Color Temperature (Nom)	Color Rendering Index (Nom)	Llmf At End Of Nominal Lifetime (Min)	Luminous Efficacy (rated) (Nom)	Luminous Flux (Nom)	Luminous Flux (Rated) (Nom)
41295950	2900	100	80	17	850	850

Operating and Electrical

order code	Lamp Current (Nom)	Voltage (Nom)	Power (Rated) (Nom)	Starting Time (Nom)	Warm Up Time To 60% Light (Nom)
41295950	4.17	12	50.0	0.0	instant full light

Approval and Application

order code	Energy Consumption kWh/ 1000 h	Energy Efficiency Label (EEL)
41295950	53	C

Mechanical and Housing

order code	Bulb Finish
41295950	Clear (CL)

Luminaire Design Requirements

order code	Bulb Temperature (Max)
41295950	250



© 2016 Philips Lighting Holding B.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2016, May 18
data subject to change